



Opoz series

Opoz 6000
POS System



iF product design award 2009



Opoz6000 is a compact size, low power consumption POS system. It is specially designed for restaurants, specialty shops and retail stores.

All-in-one design combines the host unit, monitor, MSR, and customer display together with no cable exposure. The POS even provides a printing paper slot for your promotional campaign in customer front of the machine.

Opoz 6000 The iF Product Design Award 2009.

Specifications

Host	
Mainboard	POS control mainboard
Chipset	Intel 910+NH82801
CPU	Intel CM 1.5Ghz (1M cache)
RAM	1G DDR2 on board (up to 2G)
HDD	160G 2.5" SATA HDD (or 8G DOM optional)
Power	72W/100~240V
Interface	
Serial Port	2 x external
Parallel Port	1 x external
PS/2	1 x keyboard external
VGA	1 x external
LVDS	1 x internal
USB(Support 1.1/2.0)	2 x 12V Powered USB external, 1 x 24V Powered USB external, 3 x 5V USB external
LAN	1 x 10M/100M external
Touch Monitor	
Monitor	15" TFT LCD (1024x768)
Brightness	250 cd/sq.m
Touch Panel	5 wire resistive touch panel, 35 million touches
Customer Display	
Display	2 x 20 VFD Display (5 x 7 dot matrix)
Physical Data	
Dimension	157(D) x 102(W) x 148(H)inch
Weight	19.1 lbs (N.W.)
Operation Condition	
Temperature	23 to 122F
Relative Humidity	10 to 90%