

## FORTIS XP-2000 Series

2012H / 2010H / 2008H / 2007 **Fan-free**



Clear LED indicator panel



### Printer

2" thermal printer (60mm/sec)



### MSR

2 or 3 tracks & JIS-II

## Features

- All-in-one integrated system including touch screen, thermal printer and MSR
- The most reliable Fanfree structure for harsh environment
- Thermal printer with paper jams easy to clean design
- Support Win XP Pro, POSReady, Win CE, WEPOS and Linux environment
- High quality TFT active matrix LCD panel with High resolution
- Easy tilt angle adjustment for LCD panel
- Durable resistive type touch sensor for broad range of applications
- Supports SSD (Solid-State Drive) Data Storage Device



Real mount customer pole display



12" TFT LCD, 1024x768 resolution, LED Backlight, Support touch panel



**XP-2007**



**XP-2008H**



**XP-2010H**



**XP-2012H**

Specification	XP-2007	XP-2008H	XP-2010H	XP-2012H
Processor	Intel Celeron M 600Mhz , 512K Cache			
System Memory	DDR2, SO-DIMM x 1, upgradable to 1GB			
Power Supply	+12V DC power adaptor, 60W			
OS support	Linux , WinCE , XP Pro , POSReady			
Compliance	FCC-A, CE-A, RoHs, WEEE			
Indicator LED and control panel switch	Power ON/ standby, bi-color LED, Printer Error (RED), Paper Out (RED), paper feed and power ON switch			
Printer build in	2" thermal printer (60mm/sec)			
Printer auto cutter	Option (Upgradable auto cutter)		Yes	
Paper width	58mm			
Maximum printable width	48mm max.			
<b>Display</b>				
LCD	Digital 7" TFT LCD Panel 800x600 resolution	Digital 8" TFT LCD Panel 800x600 resolution	Digital 10. 4" TFT LCD Panel 800x600 resolution	Digital 12.1" TFT LCD Panel 1024x768 resolution
Touch Sensor	N/A	5 wires resistive		
Touch Controller	N/A	USB Interface		
Tilt Adjustment	From 14° to 55°			
<b>Expansion</b>				
Storage Device	DOM, 1G (Linux or WinCE)			
<b>Connectivity</b>				
Audio Port	buzzer only			
LAN Port	10 / 100 Mb			
Serial Port	DB9 x 1			
Standard USB Port	4			
VGA Port	D-Sub 15 pin			
CR Port	Yes			
<b>Physical Dimension</b>				
Dimension (W x D x H in mm)	325 x 386.2 x 249.6 mm		325 x 386.2 x 298.1 mm	325 x 386.2 x 331.2 mm
Weight (N. W. in kg)	3.87	4.15	5.75	6.54
<b>Environment</b>				
Operation Condition	5°C~+40°C (41°F~+104°F), 20%RH~80%RH, non-condensing max. wet bulb 26°C (78.8°F)			
Storage Condition	-20°C~60°C (-4°F~140°F) , 10%RH~80%RH, non-condensing max. wet bulb 28.9°C (84.0°F)			
<b>Options</b>				
MSR	2 or 3 tracks & JIS-II			
Keyboard	84 keys mini KB with USB Interface			
Customer pole display	PD-2606: 2 x 20 VFD display / PD-330: 2 x 20 LCD Display PD-309: 2 x 20 LCD, 200mm pole / PD-2605: 2 x 20 VFD, 200mm pole PD-7614 (Simplified Chinese) / PD-7624 (Traditional Chinese) / PD-7634 (Arabic)			
SSD HDD	SATA SSD (8GB Minimum)			
2.5" SATA HDD	2.5" SATA HDD (80GB Minimum) Support XP Pro or POSReady by upgrade to SSD or 2.5" SATA HDD Storage Device			
2 <sup>nd</sup> Display	LM-2208: 8" TFT LCD ,800 x 600 resolution, LED Backlight			LM-2212: 12" TFT LCD, 1024 x 768 resolution, LED Backlight TM-2212: 12"TFT LCD, 1024 x 768 resolution, LED Backlight, Support touch panel
MSR for 2 <sup>nd</sup> Display	N/A			SD-300, Finger Printer & MSR (2 or 3 tracks & JIS-II)

❖The product information and specifications are subject to change without prior notice.

2010 V.01

**Posiflex Technology, Inc.**

6, Wu-Chuan Road, Wu Ku, Taipei, Taiwan  
Tel: 886 2 2299-1599 Fax: 886 2 2299-1819  
sales@posiflex.com.tw www.posiflex.com

